ZENITH INDUSTRIAL RUBBER PRODUCTS PVT. LTD.
Quality Rubber Solutions

GOVERNMENT OF INDIA RECOGNISED EXPORT HOUSE

PRODUCT: - NYLON FABRIC SINGLE TEXTURE BOTH SIDE NEOPRENE BLACK COATED FABRIC TECHNICAL DATA SHEET



TECHNICAL SPECIFICATION

SR NO	PROPERTY	UNIT	STANDARDS	SPECIFICATION
1	Product Code	..	...	KK-600 For Defence Application
2	Coated Fabric Thickness	MM	IS 7016 - PART I	1.30 ± 0.10
3	Coated Fabric GSM	Gram/sq. meter	IS 7016 - PART I	1550 +10% /-5 %
4	Coated Fabric Width	CMS OR MM	IS 7016 - PART I	130
5	**BREAKING STRENGTH**			
A)	Warp	Kg/50mm	IS 7016 - PART II	500
B)	Weft	Kg/50mm	IS 7016 - PART II	450
6	**ELONGATION AT BREAK**			
A)	Warp	Kg/50mm	IS 7016 - PART II	24 ± 4
B)	Weft	Kg/50mm	IS 7016 - PART II	26 ± 4
7	**TEAR STRENGTH**			
A)	Warp	Kg/50mm	IS 7016 - PART III	20
B)	Weft	Kg/50mm	IS 7016 - PART III	20
8	**PEEL SARENGTH**			
A)	Warp	Kg/50mm	IS 7016 - PART V	5 KG
B)	Weft	Kg/50mm	IS 7016 - PART V	5 KG
9	Colour		As Per Required	Black
10	Air Leak Proofness Test	Gms/Cm2	As Per Required	When tested at a pressure of 400 gms/cm2 - no leakage found
11	Polymer	..	As Per Required	Neoprene Rubber

Note: All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.*

ISO14001 : 2015 ISO 901 : 2015 45001:2018 DSIR NABL RoHS COMPLIANT REACH COMPLIANCE FDA Australian Water Quality Centre WRAS AEO INDIAN CUSTOMS