ZENITH INDUSTRIAL RUBBER PRODUCTS PVT. LTD.
Quality Rubber Solutions

GOVERNMENT OF INDIA RECOGNISED EXPORT HOUSE

PRODUCT: - ANTI WICKING FABRIC SINGLE TEXTURE COATED FABRIC TECHNICAL DATA SHEET



TECHNICAL SPECIFICATION

SR NO	PROPERTY	UNIT	STANDARDS	SPECIFICATION
1	Product Code	..	...	ANTI WICKING COATED FABRIC
2	Coated Fabric Thickness	MM	IS 7016 - PART I	0.4 MM TO 1.5 MM
3	Coated Fabric GSM	Gram/sq. meter	IS 7016 - PART I	450 GSM TO 2200 GSM
4	Coated Fabric Width	CMS OR MM	IS 7016 - PART I	140
5	**BREAKING STRENGTH**			
A)	Warp	Kg/50mm	IS 7016 - PART II	200
B)	Weft	Kg/50mm	IS 7016 - PART II	200
6	**ELONGATION AT BREAK**			
A)	Warp	Kg/50mm	IS 7016 - PART II	24 ± 6
B)	Weft	Kg/50mm	IS 7016 - PART II	26 ± 6
7	**TEAR STRENGTH**			
A)	Warp	Kg/50mm	IS 7016 - PART III	6
B)	Weft	Kg/50mm	IS 7016 - PART III	6
8	**PEEL SARENGTH**			
A)	Warp	Kg/50mm	IS 7016 - PART V	5 KG
B)	Weft	Kg/50mm	IS 7016 - PART V	5 KG
9	Colour		As Per Required	As Per Customer Requirement
10	Air Leak Test	Gms/Cm2	As Per Required	When tested at a pressure of 200 gms/cm2 - no leakage found
11	Polymer	..	As Per Required	Nitrile, Neoprene, NBR PVC, Butyl

Note: - Material Available In Different Fabric Breaking Strength.

Note: All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.*

ISO14001 : 2015 ISO 9001 : 2015